



TECHNICAL CHARACTERISTICS

senso Adjust

Total thickness	EN 428	mm	4.0
Thickness of the wear layer	EN 429	mm	0.30
Weight: Mass per unit area	EN 430	g/sqm	7600
Dimensions	EN 427	cm	15.2 x 91.4 30.5 x 61
Surface treatment	-	-	PUR+
Packaging	-	-	12 planks 10 tiles
Surface / packaging	-	sqm	planks 1.67 tiles 1.86
Norm / Product specification	-	-	EN 649
European classification	EN 685	class	23/31
VOC rating (French norm)	-	-	A+
Fire rating - Classification	EN 13501-1	class	B _{fl} -s1
Wear Group	EN 649	group	T
Impact sound insulation	EN ISO 717/2	dB	4
Room impact noise	NF S 31074	class	B
Slip resistance wet: ramp test with oil	DIN 51 130	class	R9
Dimensional stability after exposure to heat	EN 434	%	≤ 0.15
Residual indentation	EN 433	mm	≤ 0.10
Thermal conductivity	EN 12 524	W/(m.k)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Guarantee residential use	-	year	10
TVOC after 28 days	-	µg/m ³	< 100

CE MARKING



EN 14041



Areas of use: domestic use



HEALTH

- Formaldehyde-free
- Lead-free, no heavy metals
- Solvent-free
- No harmful plasticizer
- Low VOC emission
- No glue

ENVIRONMENT

- 100% recyclable
- ISO 14001
- Soapy water cleaning

